

Serial No. 09/911,437

RCA87,911/4417690

Remarks

In view of the following discussion, the applicants submit that none of the claims now pending in the application are anticipated under the provisions of 35 U. S. C. § 102, or obvious under the provisions of 35 U. S. C. § 103. Thus, the applicants believe that all of these claims are in allowable form.

REJECTIONS

A. 35 U. S. C § 102

1. Claims 1, 7 and 9 are not anticipated by Tsuruta et al.

Claims 1, 7 and 9 stand rejected under 35 U. S. C. § 102(b) as being anticipated by Tsuruta et al. (U. S. Patent 5,119,357 issued January 2, 1992). The applicants submit that these claims are not anticipated by this reference.

Claim 1 is directed to a gear rack arrangement including two resiliently braced gear racks. The two resiliently braced gear racks have suspension mountings of at least one latch hook disposed on one braced gear rack and corresponding slot-shaped openings disposed on the other one of the gear racks for providing a portion of an anti-detachment safeguard while enabling the pair of gear racks to be mutually displaceable. The anti-detachment safeguard has an elastic boss disposed on at least one of the gear tracks in order to prevent detachment of the other gear rack when suspension mountings are in a position with respect to the slot-shaped openings so the latch hooks are slideably disposed in the slot-shaped openings.

In Tsuruta et al., the projection between two 5a in Fig. 3 neither forms an anti-detachment safeguard nor has a locking end portion 5b, as it especially becomes clear from FIGS. 20 to 24 and the description (column 5, lines 24 to 34). According to Tsuruta et al. at column 5, lines 24 to 34 and as shown in

Serial No. 09/911,437

RCA87,911/4417690

FIGS. 3, 10 and 20 to 24 "the first rack 5 is provided with a pair of projections 5a, 5a each having an engaging portion 5b with an enlarged end". However, the projection between said two 5a has no enlarged end, which could prevent the rack 6 from slipping off in the small area of slots 6a. Consequently, the projection between two 5a cannot form an anti-detachment safeguard because slipping off is only prevented by the enlarged ends of the projections 5a in the small area of slots 6a. The spring 7 is provided for biasing the second rack 6 leftward relative to the first rack 5, however, cannot prevent from shipping off. Due to the fact that the projection between two 5a is free moveable in a slot over a distance D2, which is larger than a distance D1 over which the enlarged ends of projections 5 prevent from shipping off, the projection between two 5a independent whether or not it is elastic cannot prevent from shipping off (see e.g. D1 and D2 in FIGS. 20 and 24). Said projection or so-called elastic boss between two 5a has no influence on slipping off and also neither in the narrow portion of 6a nor in the position with respect to the slot-shaped openings where the latch hooks being first slide into the wide portion of 6a in assembly and therefore never can be called or has a function of an anti-detachment safeguard.

However, the elastic boss E according to applicants invention prevent detachment also in the wide portion of the slot where the latch hooks being first slide in. In Tsuruta et al., neither the elastic boss between the two 5a nor the spring 7 according to prevent the rack 6 from shipping off in the wide portion of the slot shaped openings 6a.

Claims 7 and 9 depend directly from claim 1 or recite similar subject matter. As such, the applicants submit that claims 7 and 9 are also patentable over Tsuruta et al.

Serial No. 09/911,437

RCA87,911/4417690

B. 35 U. S. C. § 103

1. Claim 6 is not obvious over Tsuruta et al. in view of Ikedo et al.

Claim 6 stands rejected under 35 U. S. C. § 103(a) as being unpatentable over Tsuruta et al. (U. S. Patent 5,119,357 issued January 2, 1992) in view of Ikedo et al. (U. S. Patent 4,631,716 issued December 23, 1986). The applicants submit that this claim is not rendered obvious by the combination of these references.

Claim 6 is directed to a gear rack arrangement including two resiliently braced gear racks. The two resiliently braced gear racks have suspension mountings of at least one latch hook disposed on one braced gear rack and corresponding slot-shaped openings disposed on the other one of the gear racks for providing a portion of an anti-detachment safeguard while enabling the pair of gear racks to be mutually displaceable. The anti-detachment safeguard has an elastic deformable boss disposed on at least one of the gear tracks in order to prevent detachment of the other gear rack when suspension mountings are in a position with respect to the slot-shaped openings so the latch hooks are slideably disposed in the slot-shaped openings.

In Tsuruta et al., the projection between two 5a in Fig. 3 neither forms an anti-detachment safeguard nor has a locking end portion 5b, as it especially becomes clear from FIGS. 20 to 24 and the description (column 5, lines 24 to 34). According to Tsuruta et al. at column 5, lines 24 to 34 and as shown in FIGS. 3, 10 and 20 to 24 "the first rack 5 is provided with a pair of projections 5a, 5a each having an engaging portion 5b with an enlarged end". However, the projection between said two 5a has no enlarged end, which could prevent the rack 6 from slipping off in the small area of slots 6a. Consequently, the projection between two 5a cannot form an anti-detachment safeguard because slipping off is only prevented by the enlarged ends of the projections 5a in the small area of slots 6a. The spring 7 is provided for biasing the second rack 6 leftward relative

Serial No. 09/911,437

RCA87,911/4417690

to the first rack 5, however, cannot prevent from shipping off. Due to the fact that the projection between two 5a is free moveable in a slot over a distance D2, which is larger than a distance D1 over which the enlarged ends of projections 5 prevent from shipping off, the projection between two 5a independent whether or not it is elastic cannot prevent from shipping off (see e.g. D1 and D2 in FIGS. 20 and 24). Said projection or so-called elastic boss between two 5a has no influence on slipping off and also neither in the narrow portion of 6a nor in the position with respect to the slot-shaped openings where the latch hooks being first slide into the wide portion of 6a in assembly and therefore never can be called or has a function of an anti-detachment safeguard.

However, the elastic boss E according to applicants invention prevent detachment also in the wide portion of the slot where the latch hooks being first slide in. In Tsuruta et al., neither the elastic boss between the two 5a nor the spring 7 according to prevent the rack 6 from shipping off in the wide portion of the slot shaped openings 6a.

Ikedo et al. teaches a rack which is made of resin (column 6, line 55). However, applicants boss in claim 6 is elastically deformable. Ikedo et al. gives no hint to a elastically deformable rack.

Thus, claim 6 is patentable over the combination of these references.

#### CONCLUSION


Thus, the applicants submit that none of the claims, presently in the application are anticipated under the provisions of 35 U. S. C. § 102, or obvious under the provisions of 35 U. S. C. § 103. Consequently, the applicants believe that all of the claims are presently in condition for allowance. Accordingly, both reconsideration of this application and its swift passage to issue are earnestly solicited.

Serial No. 09/911,437

RCA87,911/4417690

If, however, the Examiner believes that there are any unresolved issues requiring adverse final action in any of the claims now pending in the application, it is requested that the Examiner telephone Ms. Patricia A. Verlangieri, at (609) 734-6867, so that appropriate arrangements can be made for resolving such issues as expeditiously as possible.

Respectfully submitted,

  
Patricia A. Verlangieri, Attorney  
Reg. No. 42,201  
(609) 734-6867

Thomson Inc.  
P. O. Box 5312  
Princeton, New Jersey 08543-5312

December 22, 2004

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**